

F-SERIES

Specification Sheet

FVM 1200



www.isuzu.co.za f  

ISUZU

With you, for the long run

MODEL	FVM 1200
AXLE LAYOUT	6X2
CONTROL	FORWARD
MASS	
Permissible Body + Payload (kg)	17370
Tare - Total (T) (kg)	6630
Tare - Front (kg)	3190
Tare - Rear (kg)	3440
GVM (kg)	24000
V (kg)	24000
GCM (kg)	32000
D/T (kg)	32000
Axle - Front GA/GAU (kg)	7100
Axle - Front A/AU (kg)	7100
Axle - Rear GA/GAU (kg)	10500
Axle - Rear A/AU (kg)	18000
Litres of Fuel Tank 1 Included in Tare (litres)	15
Litres of Fuel Tank 2 Included in Tare (litres)	15
Tools Included in Tare	Jack, Warning Triangle, Basic Tool Kit
Spare Wheel Included in Tare	Yes
Fifth Wheel Included in Tare	No
PERFORMANCE	
Gradeability at V (%)	25
Gradeability at D/T (%)	19
Max. Geared Road Speed (km/h)	108
MAJOR DIMENSIONS	
Overall Length (mm)	9730
Overall Width (mm)	2400
Wheelbase (mm)	5700
CA - Cab to Bogie / Rear Axle (mm)	5074
CE - Cab to End of Chassis (mm)	7664
OH - Overall Height (mm)	2790
FOH - Front Overhang (mm)	1440
ROH - Rear Overhang (mm)	2590
Rear Axle Bogie Spacing (mm)	1300
1/2 Rear Axle Bogie Spacing (mm)	650
EH - Chassis Rear End Height (mm)	1070

MODEL	FVM 1200
AXLE LAYOUT	6X2
CONTROL	FORWARD
MAJOR DIMENSIONS	
HH - Ground Clearance (mm)	257
Chassis Width - Rear (mm)	850
Turning Radius - Curb to Curb (mm)	9200
Turning Radius - Wall to Wall (mm)	10200
ENGINE	
Make	Isuzu
Model	6HK1-TCN
Capacity (cm ³)	7790
Layout	Diesel Inline-6
Type	Turbocharged Intercooled Common Rail
Power @ r/min (kW)	176 @ 2400
Torque @ r/min (Nm)	706 @ 1450 - 2400
Emissions Standard	Euro 2
CLUTCH	
Make	Exedy
Model	380
Type	Single
Diameter	380
Operation	Hydraulic Air-Assisted
TRANSMISSION	
Make	ZF
Model	6 S 1000
Type	Synchromesh
Shift	Manual Gearshift
No. of Gears Forward	6
First Gear Ratio : 1	6.75
Top Gear Ratio : 1	0.78
PTO (Power Take-Off)	Optional
DRIVE AXLE	
Make	Isuzu
Model Axle Front	D108
Model Drive Axle Rear	F071
Reduction Type	Single

MODEL	FVM 1200
AXLE LAYOUT	6X2
CONTROL	FORWARD
DRIVE AXLE	
Final Ratio : 1	6.429
SUSPENSION	
Front	Multi-Leaf Springs
Rear	Multi-Leaf Springs
Shock Absorbers	Front
Stabilisers	Front
STEERING	
Operation	Power
BRAKES	
System Type	Full Air
Front	Drums
Rear	Drums
Anti-Lock Braking System (ABS)	Standard
Park / Emergency System	Spring
Exhaust Brake	Standard
Engine Brake	No
Retarder	No
ELECTRICAL & FUEL	
Fuel Tank 1 Capacity (litres)	400
Fuel Tank 2 Capacity (litres)	0
TYRES	
Size & Ply Rating - Front	11 R22.5-16PR
Size & Ply Rating - Rear	11 R22.5-16PR
CAB & EXTRAS	
Type	Medium
Roof	Low
No. of Bunks	0
No. of Seats	3
Air-Conditioning	Optional
Radio/CD	Optional
Tachograph	Optional
On-Board Computer	No
Tilt Cab	Yes

The information above is provided as a guide only. Specification is subject to change at any time. Please contact your nearest dealer to confirm current specification. Model/s shown may differ. E&OE. Date of print January 2018.