

FOURTRAX 420

Optimised with Computer Aided Design (CAD) to deliver best-in-class handling and all day comfort – the versatile Fourtrax 4wd really sets the standard, making daily tasks both easier and more enjoyable. Its rugged utility styling and tough double-cradle chassis offer exceptional

durability and handling. Its multi-function LCD display provides the driver with key information at a glance, whilst the adjustable pre-load front and rear suspension lets you tailor the ride to the terrain and conditions.



Fourtrax 420 DCT PS

TRX420FA2

Utility work ATV	4WD
Engine Size	420 cc
Engine Type	Liquid-cooled, wet-sump, longitudinally mounted OHV 4-stroke single cylinder
Bore x Stroke	86.5 mm x 71.5 mm
Fuel System	PGM-FI, 34 mm throttle-body fuel-injection system
Ignition	Full-transistorised type with electronic advance
Starter	Electric / Recoil
Gears	Five forward gears plus reverse
Transmission	Automatic Dual Clutch Transmission (DCT) with auto-shifting or electric shift
Drive	4wd Direct drive-shafts with TraxLok® switchable 2wd/4wd and locking front differential
Power Steering	Power Steering
Front Suspension	Independent double wishbone
Rear Suspension	Swingarm with single shock
Adjustable Pre-load	Front and Rear suspension
Suspension Travel	Front: 170 mm Rear: 170 mm
Front Brakes	190 mm dual hydraulic discs
Rear Brake	160 mm sealed mechanical drum
Tyres	Front: 24 x 8-12 Rear: 24 x 10-11
Dimensions	L: 2103 mm W: 1204 mm H: 1176 mm
Wheelbase	1270 mm
Seat Height	855 mm
Ground Clearance	183 mm
Min. Turning Radius	2.8 m
Fuel Capacity	14.7 L, incl. 4.9 L reserve
Bed Capacity	Front: 29.9 kg / Rear: 60 kg
Towing capacity	384 kg
Dry weight	291 kg
Colours	Red

Fourtrax 420 DCT IRS PS

TRX420FA6

Utility work ATV	4WD
Engine Size	420 cc
Engine Type	Liquid cooled, wet-sump, longitudinally mounted OHV 4-stroke single cylinder
Bore x Stroke	86.5 mm x 71.5 mm
Fuel System	PGM-FI, 34 mm throttle-body fuel-injection system
Ignition	Full-transistorised type with electronic advance
Starter	Electric / Recoil
Gears	Five forward gears plus reverse
Transmission	Automatic Dual Clutch Transmission (DCT) with auto-shifting or electric shift
Drive	4wd Direct drive-shafts with TraxLok® switchable 2wd/4wd and locking front differential
Power Steering	Power Steering
Front Suspension	Independent double wishbone
Rear Suspension	Dual A-Arm (IRS)
Adjustable Pre-load	Front and Rear suspension
Suspension Travel	Front: 185 mm Rear: 215 mm
Front Brakes	190 mm dual hydraulic discs
Rear Brake	170 mm single hydraulic disc
Tyres	Front: 24 x 8-12 Rear: 24 x 10-11
Dimensions	L: 2146 mm W: 1204 mm H: 1203 mm
Wheelbase	1295 mm
Seat Height	901 mm
Ground Clearance	246 mm
Min. Turning Radius	3.5 m
Fuel Capacity	14.7 L, incl. 4.9 L reserve
Bed Capacity	Front: 29.9 kg / Rear: 60 kg
Towing capacity	384 kg
Dry weight	300 kg
Colours	Red