

F-SERIES

*Specification
Sheet*

FSR 800 SWB



www.isuzu.co.za f  

ISUZU

With you, for the long run

MODEL	FSR 800 SWB
AXLE LAYOUT	4X2
CONTROL	FORWARD
MASS	
Permissible Body + Payload (kg)	9760
Tare - Total (T) (kg)	3740
Tare - Front (kg)	2300
Tare - Rear (kg)	1440
GVM (kg)	13500
V (kg)	13500
GCM (kg)	18000
D/T (kg)	18000
Axle - Front GA/GAU (kg)	5000
Axle - Front A/AU (kg)	5000
Axle - Rear GA/GAU (kg)	9000
Axle - Rear A/AU (kg)	9000
Litres of Fuel Tank 1 Included in Tare (litres)	15
Litres of Fuel Tank 2 Included in Tare (litres)	0
Tools Included in Tare	Jack, Warning Triangle, Basic Tool Kit
Spare Wheel Included in Tare	Yes
PERFORMANCE	
Gradeability @ V (%)	36
Gradeability @ D/T (%)	27
Max. Geared Road Speed (km/h)	120
MAJOR DIMENSIONS	
Overall Length (mm)	6560
Overall Width (mm)	2120
Wheelbase (mm)	3790
CA - Cab to Bogie/Rear Axle (mm)	2894
CE - Cab to End of Chassis (mm)	4494
OH - Overall Height (mm)	2790
FOH - Front Overhang (mm)	1170
ROH - Rear Overhang (mm)	1600
Rear Axle Bogie Spacing (mm)	N/A
1/2 Rear Axle Bogie Spacing (mm)	N/A
EH - Chassis Rear End Height (mm)	915

MODEL	FSR 800 SWB
AXLE LAYOUT	4X2
CONTROL	FORWARD
MAJOR DIMENSIONS	
HH - Ground Clearance (mm)	221
Chassis Width - Rear (mm)	840
Turning Radius - Curb to Curb (mm)	6800
Turning Radius - Wall to Wall (mm)	7600
ENGINE	
Make	Isuzu
Model	6HK1-TCN
Capacity (cm ³)	7790
Layout	Diesel Inline-6
Type	Turbocharged Intercooled Common Rail
Power @ r/min (kW)	176 @ 2400
Torque @ r/min (Nm)	706 @ 1450 - 2400
Emissions Standard	Euro 2
CLUTCH	
Make	Exedy
Model	380
Type	Single
Diameter (mm)	380
Operation	Hydraulic Air-Assisted
TRANSMISSION	
Make	Isuzu
Model	MZW6P
Type	Synchromesh
Shift	Manual Gearshift
No. of Gears Forward	6
First Gear Ratio : 1	6.615
Top Gear Ratio : 1	0.722
PTO (Power Take-Off)	Optional
DRIVE AXLE	
Make	Isuzu
Model Axle Front	R090
Model Drive Axle Rear	F050
Reduction Type	Single

MODEL	FSR 800 SWB
AXLE LAYOUT	4X2
CONTROL	FORWARD
DRIVE AXLE	
Final Ratio : 1	4.555
SUSPENSION	
Front	Multi-Leaf Springs
Rear	Multi-Leaf Springs
Shock Absorbers	Front
Stabilisers	Front
STEERING	
Operation	Power
BRAKES	
System Type	Air Over Hydraulic
Front	Drums
Rear	Drums
Anti-Lock Braking System (ABS)	Standard
Park / Emergency System	Spring
Exhaust Brake	Standard
Engine Brake	No
Retarder	No
ELECTRICAL & FUEL	
Fuel Tank 1 Capacity (litres)	200
Fuel Tank 2 Capacity (litres)	0
TYRES	
Size & Ply Rating - Front	265 / 70 R19.5
Size & Ply Rating - Rear	265 / 70 R19.5
CAB & EXTRAS	
Type	Medium
Roof	Low
No. of Bunks	0
No. of Seats	3
Air-Conditioning	Optional
Radio/CD	Optional
Tachograph	Optional
On-Board Computer	No
Tilt Cab	Yes

The information above is provided as a guide only. Specification is subject to change at any time. Please contact your nearest dealer to confirm current specification. Model/s shown may differ. E&OE. Date of print January 2018.