

FOREMAN 520

THE ALL-ROUND WORK HORSE

A hard hitting ATV designed to make tough work easy.

Big loads, long days – no problem. The Honda Foreman is built to deliver solid handling and powerful performance with renowned durability, whatever the conditions. With huge low down torque delivered by a new, larger fuel efficient liquid-cooled 518 cc engine,



FOREMAN MODELS (4WD)

Foreman 520 PS

TRX520FM2, TRX520FE2 (ES)

Heavy duty ATV

4WD

Engine Size	518 cc
Engine Type	Liquid-cooled, wet-sump, longitudinally mounted OHV 4-stroke single cylinder
Bore x Stroke	96.0 mm x 71.5 mm
Fuel System	PGM-FI, 36 mm throttle-body
Ignition	Full-transistorised type with electronic advance
Starter	Electric
Gears	Five forward gears plus reverse
Transmission	Auto clutch with manual ES: electric shift
Drive	4wd Direct drive-shafts with TraxLok® switchable 2wd/4wd and locking front differential
Power Steering	Power Steering
Front Suspension	Independent double-wishbone
Rear Suspension	Swingarm with single shock
Adjustable Pre-load	Front and Rear suspension
Suspension Travel	Front: 185 mm Rear: 215 mm
Front Brakes	190 mm dual hydraulic discs
Rear Brake	170 mm sealed mechanical drum
Tyres	Front: 25 x 8-12 Rear: 25 x 10-12
Dimensions	L: 2185 mm W: 1204 mm H: 1237 mm ES: L: 2103 mm W: 1204 mm H: 1220 mm
Wheelbase	1270 mm
Seat Height	924 mm ES: 869 mm
Ground Clearance	248 mm
Min. Turning Radius	3.5 m
Fuel Capacity	14.7 L, incl. 4.9 L reserve
Rack capacity	Front: 44.9 kg / Rear: 84.8 kg
Towing capacity	384 kg
Dry weight	283 kg ES: 285 kg
Colours	Red

Foreman 520 IRS PS

TRX520FM6

Heavy duty ATV

4WD

Available in Green*

Engine Size	518 cc
Engine Type	Liquid-cooled, wet-sump, longitudinally mounted OHV 4-stroke single cylinder
Bore x Stroke	96.0 mm x 71.5 mm
Fuel System	PGM-FI, 36 mm throttle-body
Ignition	Full-transistorised type with electronic advance
Starter	Electric
Gears	Five forward gears plus reverse
Transmission	Auto clutch with manual shift
Drive	4wd Direct drive-shafts with TraxLok® switchable 2wd/4wd and locking front differential
Power Steering	Power Steering
Front Suspension	Independent double-wishbone
Rear Suspension	Dual A-Arm (IRS)
Adjustable Pre-load	Front and Rear suspension
Suspension Travel	Front: 185 mm Rear: 215 mm
Front Brakes	190 mm dual hydraulic discs
Rear Brake	170 mm single hydraulic disc
Tyres	Front: 25 x 8-12 Rear: 25 x 10-12
Dimensions	L: 2185 mm W: 1204 mm H: 1240 mm
Wheelbase	1293 mm
Seat Height	919 mm
Ground Clearance	251 mm
Min. Turning Radius	3.5 m
Fuel Capacity	14.7 L, incl. 4.9 L reserve
Rack capacity	Front: 44.9 kg / Rear: 84.8 kg
Towing capacity	599 kg
Dry weight	304 kg
Colours	Red / Green (*+£200 Ex. VAT)