

FOREMAN 520

and its computer engineered chassis providing smooth, sure footed handling, the Foreman truly is a joy to ride. Its thick padded saddle makes it easier to tackle a long day out in the field, and the unique Honda TraxLok® allows switchable 2/4wd and push-button full differential lock to give improved traction, even in deep mud.



Foreman 520 DCT IRS PS

TRX520FA6

Heavy duty ATV	4WD
Engine Size	518 cc
Engine Type	Liquid-cooled, wet-sump, longitudinally mounted OHV 4-stroke single cylinder
Bore x Stroke	96.0 mm x 71.5 mm
Fuel System	PGM-FI, 36 mm throttle-body
Ignition	Full-transistorised type with electronic advance
Starter	Electric
Gears	Five forward gears plus reverse
Transmission	Automatic Dual Clutch Transmission (DCT) with auto-shifting or electric shift
Drive	4wd Direct drive-shafts with TraxLok® switchable 2wd/4wd and locking front differential
Power Steering	Power Steering
Front Suspension	Independent double-wishbone
Rear Suspension	Dual A-Arm (IRS)
Adjustable Pre-load	Front and Rear suspension
Suspension Travel	Front: 185 mm Rear: 215 mm
Front Brakes	190 mm dual hydraulic discs
Rear Brake	170 mm single hydraulic disc
Tyres	Front: 25 x 8-12 Rear: 25 x 10-12
Dimensions	L: 2185 mm W: 1204 mm H: 1237 mm
Wheelbase	1293 mm
Seat Height	922 mm
Ground Clearance	248 mm
Min. Turning Radius	3.5 m
Fuel Capacity	14.7 L, incl. 4.9 L reserve
Rack capacity	Front: 44.9 kg / Rear: 84.8 kg
Towing capacity	599 kg
Dry weight	318 kg
Colours	Red

PIONEER 520

THE COMPACT UTV

Small but mighty, with a slim profile allowing you and a passenger to go places other UTVs can't.



Pioneer 520
Two seats



UTV MODELS (4WD)

Pioneer 520

SXS520

Heavy duty UTV	4WD	Two seats
Engine Size	518 cc	
Engine Type	Liquid-cooled, wet-sump, longitudinally mounted OHV 4-stroke single cylinder	
Bore x Stroke	96.0 mm x 71.5 mm	
Fuel System	PGM-FI, 36 mm throttle-body	
Ignition	Full-transistorised type with electronic advance	
Starter	Electric	
Gears	Five forward gears with reverse	
Transmission	Automatic with auto or manual shift modes	
Drive	4wd Direct drive-shafts with switchable 2wd/4wd and locking front differential	
Power Steering	–	
Front Suspension	Independent double-wishbone	
Rear Suspension	Independent double-wishbone (IRS)	
Adjustable Pre-load	Rear suspension	
Suspension Travel	Front: 147 mm Rear: 150 mm	
Front Brakes	Dual 200 mm hydraulic discs	
Rear Brake	170 mm hydraulic disc	
Tyres	Front: 24 x 8-12 Rear: 24 x 10-12	
Dimensions	L: 2667 mm W: 1270 mm H: 1808 mm	
Wheelbase	1854 mm	
Seat Height	703 mm	
Ground Clearance	216 mm	
Min. Turning Radius	3.9 m	
Fuel Capacity	15.5 L, incl. 4.2 L reserve	
Bed Capacity	204 kg	
Towing capacity	454 kg	
Dry weight	469 kg	
Colours	Red	