

# HONDA CRF450 R

## MY 2017

### ENGINE

Engine Type:	449.7cc liquid-cooled single-cylinder four-stroke
Bore x Stroke:	96.0mm x 62.1mm
Compression Ratio:	13.5:1
Induction:	Programmed fuel-injection system (PGM-FI); 46mm throttle bore
Ignition:	Full transistorized ignition
Transmission:	Constant-mesh 5-speed return
Final Drive:	520 chain; 13T/49T
Valve Train:	Unicam® OHC, four-valve; 10.0mm intake, steel; 8.8mm exhaust, steel

### SUSPENSION

Front:	49mm fully adjustable leading-axle inverted telescopic
Rear:	Showa coil-spring fork; 12.0 in. travel Pro-Link swing arm system; fully adjustable Showa single shock; 12.4 in. travel

### BRAKES

Front:	Single 260mm hydraulic disc
Rear:	Single 240mm hydraulic disc

### TIRES

Front:	Dunlop Geomax MX3S 80/100-21 55M with tube
Rear:	Dunlop Geomax MX3S 120/80-19 55M with tube
Rake (Caster Angle):	27° 22'
Trail:	116.0mm (4.6 in.)
Seat Height:	37.8 in.
Ground Clearance:	12.9 in.
Wheelbase:	58.3 in.
Fuel Capacity:	1.6 gal.
Color:	Red
Curb Weight*:	243 lbs.



**HONDA**